



NOTES:

1. ALUMINUM CONSTRUCTION
2. BUNA N SEALS
3. BOROSILICATE GLASS WITH REDLINE ON WHITE BACKGROUND
4. DUAL SCALE THERMOMETER, 50° TO 300° F AND 10° TO 150° C.
5. 250°F (121°C) MAX TEMPERATURE
6. 290 PSI (2 MPa) MAX PRESSURE AT 150°F (65°C) AND NO CORROSION
7. RESERVOIR MUST BE DRAINED TO REMOVE DIAL THERMOMETER OR LOSS OF FLUID WILL OCCUR
8. DIMENSIONS IN [] ARE mm

THIS DOCUMENT CONTAINS INFORMATION PROPRIETARY TO LDI Industries, Inc. AND IS FURNISHED UPON THE EXPRESS CONDITION THAT THE INFORMATION CONTAINED HEREIN WILL NOT BE DISCLOSED TO ANY THIRD PARTY OR USED DIRECTLY OR INDIRECTLY IN ANY WAY DETRIMENTAL TO THE INTEREST OF LDI Industries, Inc.



TITLE GAGE_FMNT_THERM_5.00_AL_F_NBR

DWG NO./ITEM NO. G615-05-A-1C_REF

MATERIAL	SEE NOTES		
FINISH	NONE		
NOM WT (LB)	1.428		
REV	DATE	ECN NO.	BY

TOLERANCES	ALL DIMENSIONS ARE FOR REF ONLY
SCALE	11/16
DO NOT SCALE DRAWING	

DRWN	BMK	DATE	05/27/14	CHKD	BMK	DATE	05/27/14	SHT	1/1	REV	-
------	-----	------	----------	------	-----	------	----------	-----	-----	-----	---