3/8-16 BOLTS COVER TIE DOWN LUGS NOTES: 1. THIS RESERVOIR IS DESIGNED FOR STATIONARY INSTALLATIONS, MOBILE INSTALLATIONS ARE SUBJECT TO FACTORY REVIEW. 2. THIS RESERVOIR IS THOROUGHLY CLEANED, A PRESERVATIVE APPLIED, AND PRIME PAINTED GRAY PRIOR TO SHIPMENT. ANY SUBSEQUENT CUTTING OR WELDING ON THE UNIT COULD CAUSE CONTAMINATION AND MAY VOID THE WARRANTY. 3. OPERATING TEMPERATURE IS 180° F MAXIMUM. FOR HIGHER TEMPERATURES CONSULT FACTORY.
4. ALL PORTS ARE PLASTIC PLUGGED AND PROTECTED FOR SHIPPING. LEAVE THESE IN PLACE UNTIL THE UNIT (18.00) IS FINAL PAINTED OR FINISH ASSEMBLED. IF PAINTED AFTER ASSEMBLY, PLUG AND PROTECT ALL OPENINGS INTO THE RESERVOIR. 5. SHIPPED LOOSE ITEMS: (5145G) GASKET; (GT623-05-PGN-1C) SIGHT GAGE; (836025) BOLTS; (PFH60-8) PLUG 6. RECOMMENDED ASSEMBLY TORQUE: ENDCOVER (15 FT LB), SIGHT GAGE (80 IN LB) 7. COVER PLATE (SERIES 1, 2, 2A, OR 3) ORDER AS SEPARATE ITEM \emptyset .56 (4 PLCS) 20.50 MTG HOLES **CHANNEL** SIGHT GAGE 17.50 SQ **GASKET** GT623-05-PGN-1C 5.00 (18.12) 1/2 NPT DRAIN WITH PLUG (1.50) (15.00 (19.00) **-**√ .75`) (.75)----ALL DIMENSIONS FOR REFERENCE ONLY UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES NAME DATE 06/17/2019 DRAWN BY MAT RES VERT 20GAL STL PRM CHECKED BY 06/18/2019 BMK REVISED BY 06/20/2019 MAT Industries THIS DOCUMENT CONTAINS INFORMATION PROPRIETARY TO LDI INDUSTRIES, INC. AND IS FURNISHED UPON THE EXPRESS CONDITION THAT THE MANITOWOC, WI INFORMATION CONTAINED HEREIN WILL HUNTLEY, IL SIZE DWG. NO. **REV** NOT BE DISCLOSED TO ANY THIRD PARTY MATERIAL OR USED DIRECTLY OR INDIRECTLY IN ANY V215174 REF WAY DETRIMENTAL TO THE INTEREST OF FINISH SEE NOTES & BOM LDI INDUSTRIES, INC. DO NOT SCALE DRAWING SCALE: 1:8 WT(LB): 55.88 SHT 1 OF 1 **CUST NO** 3