3/8-16 BOLTS **COVER TIE DOWN LUGS** 1. THIS RESERVOIR IS DESIGNED FOR STATIONARY INSTALLATIONS, MOBILE INSTALLATIONS ARE SUBJECT TO FACTORY REVIEW. 2. THIS RESERVOIR IS THOROUGHLY CLEANED, A PRESERVATIVE APPLIED, AND PRIME PAINTED GRAY PRIOR TO SHIPMENT. ANY SUBSEQUENT CUTTING OR WELDING ON THE UNIT COULD CAUSE CONTAMINATION AND MAY VOID THE WARRANTY. 3. OPERATING TEMPERATURE IS 180° F MAXIMUM. FOR HIGHER TEMPERATURES CONSULT FACTORY. 4. ALL PORTS ARE PLASTIC PLUGGED AND PROTECTED FOR SHIPPING. LEAVE THESE IN PLACE UNTIL THE UNIT 18.00 IS FINAL PAINTED OR FINISH ASSEMBLED. IF PAINTED AFTER ASSEMBLY, PLUG AND PROTECT ALL OPENINGS INTO THE RESERVOIR. 5. SHIPPED LOOSE ITEMS: (5145G) GASKET; (GT623-05-PGN-1C) SIGHT GAGE; (836025) BOLTS; (PFH60-8) PLUG 6. RECOMMENDED ASSEMBLY TORQUE: ENDCOVER (15 FT LB), SIGHT GAGE (80 IN LB) 7. COVER PLATE (SERIES 1, 2, 2A, OR 3) ORDER AS SEPARATE ITEM _____ \emptyset .56 (4 PLCS) 20.50 MTG HOLES **CHANNEL** (17.50 SQ) **GASKET** SIGHT GAGE GT623-05-PGN-1C 5.00 (26.12)1/2 NPT DRAIN WITH PLUG ALL DIMENSIONS FOR REFERENCE ONLY (19.00) (1.50) (15.00) (.75)→ .75) UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES NAME DATE DRAWN BY MAT 06/17/2019 RES VERT 30GAL STL PRM 06/18/2019 CHECKED BY BMK REVISED BY Industries THIS DOCUMENT CONTAINS INFORMATION PROPRIETARY TO LDI INDUSTRIES, INC. AND IS FURNISHED UPON THE EXPRESS CONDITION THAT THE MANITOWOC, WI INFORMATION CONTAINED HEREIN WILL HUNTLEY, IL REV SIZE DWG. NO. NOT BE DISCLOSED TO ANY THIRD PARTY MATERIAL OR USED DIRECTLY OR INDIRECTLY IN ANY V215175 REF WAY DETRIMENTAL TO THE INTEREST OF FINISH SEE NOTES & BOM LDI INDUSTRIES, INC. DO NOT SCALE DRAWING SCALE: 1:8 WT(LB): 74.48 SHT 1 OF 1 **CUST NO** 3 2