P UGS

LSP501 SERIES

The LSP501 Series low pressure aluminum sight plug has a clear glass or polycarbonate sight and a reflector machined into the plug body. Sight options include screen printed level lines. An economical alternative to threaded sight plugs requiring only a reamed hole or equivalent to provide a secure fit. Box quantities may apply.

Standard Features:

- Sight: Clear or with level lines
- Available in sight material and level line combinations


Standard Materials:

- Aluminum construction
- Buna N seals (other seal material is available please specify)
- Soda lime glass or polycarbonate sight material

Temperature and Pressure Ratings:

- Maximum operating temperature up to 180°F (82°C). (For applications requiring maximum operating temperatures in excess of 180°F (82°C), consult factory for available options.)
- 25 psi (172 kPa) maximum operating pressure at 69°F (20°C)

CAUTION: • Not recommended for steam applications · Scratched glass significantly reduces the pressure rating of the sight plug



NOTE: All dimensions are inches [mm]

LSP501 Series					
Part No.			А	в	с
No Fluid Level Line	With Fluid Level Line	Min/Mult Box Quantity	inches (mm)	inches (mm)	inches (mm)
-	LSP501-07RPL	25	.878 (22.301)	.875 (22.225)	.55 (13.97)
-	LSP501-08RGL	25	1.003 (25.476)	1.000 (25.400)	.66 (16.76)
-	LSP501-10RPL	25	1.253 (31.826)	1.250 (31.750)	.75 (19.05)
-	LSP501-12RPL	15	1.503 (38.176)	1.500 (38.100)	1.00 (25.40)
LSP501-16RP	-	15	2.003 (50.876)	2.000 (50.800)	1.56 (39.62)

Suffixes

Reflector = RP


Reflector, polycarb sight =

RGL = Reflector, glass sight , level line

Reflector, polycarb sight, level RPL =

Dimensions and specifications are subject to change without notice. Not all items are Made-To-Stock, contact us for availability.

R





sales@ldi-industries.com www.ldi-industries.com

02/14